

Delphion

[RESEARCH](#) [INTEGRATED IAM](#) [SERVICES](#) [INSIDE DELPHION](#)

[Log Out](#) | [Work Files](#) | [Saved Searches](#)

[My Account](#) | [Products](#) | [News](#) | [Events](#)

Search: [Quick/Number](#) [Boolean](#) [Advanced](#)

The Delphion Integrated View

Buy Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: [Create new Work File](#)

View: [INPADOC](#) | Jump to: Top | Go to: [Derwent...](#)

☒ Email th

Title: **JP11164035A2: REMOTE MONITORING SYSTEM**

Country: **JP** Japan
Kind: **A**

Inventor: **KUMAKI KAZUYUKI;**


Assignee: **MEIDENSHA CORP**
[News, Profiles, Stocks and More about this company](#)

Published / Filed: **June 18, 1999 / Nov. 27, 1997**

Application Number: **JP1997000325539**

IPC Code: **H04M 11/00; G06F 13/00; G09G 5/00; G09G 5/00; H04L 12/54; H04L 12/58; H04N 7/18; H04Q 9/00;**

Priority Number: **Nov. 27, 1997 JP19971997325539**



Abstract:


PROBLEM TO BE SOLVED: To provide a remote monitoring system with which versatility is improved and cost down can be attained.

SOLUTION: A central processing unit(CPU) 3 on the central side and a general-purpose personal computer(PC) 11 on the terminal side are connected by an ISDN line or private LAN, the general-purpose PC loads an internet browser software and receives a real time access program from the CPU while using this software, and the change of a display picture is performed by using this program. The CPU transmits the real time access program to a remote terminal when accessing the remote terminal, holds display information in an HTTP format and periodically changes only the changed part of the display information. The general-purpose PC 11 is used for transmitting image data between the remote side and the job site side as well.

COPYRIGHT: (C)1999,JPO

Family: None

Other Abstract Info: None



[Nominate](#)

[this for the Gallery...](#)